





The Patent Office Concept House Cardiff Road Newport South Wales NP10 8QQ

CERTIFIED COPY OF PRIORITY DOCUMENT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 31 March 2004

Patents Form 7/77
Patents Act 1977

(Rule 15)

The Patent Office

2 7 AUG 2002

Statement of inventorship and of right to grant of a patent

The Patent Office
Cardiff Road
Newport
South Wales NP10 8QQ

1. Your reference 1882301/KB 2. Patent Application Number accompanying application reference 1882301 0219876.0 3. Full name of the or each applicant Sensopad Technologies Limited 4. Title of the invention CONCEPT FOR AUTOMOTIVE STEERING WHEELS 5. State how the applicant(s) derived the right from the inventor(s) to be granted a patent By virtue of the employment of the inventors 6. How many, if any additional Patents Forms 7/77 are attached to this form? None 7. I/We believe that the person(s) named over the page (and on any extra copies of this form) is/are the inventor(s) of the invention which the above patent application relates to. Date 27 August 2002 8. . Name and daytime telephone number of BRINCK; David John Borchardt person to contact in the United Kingdom Tel: 020 7831 2290

Patents Form 7/77

MACAULAY; Bruce c/o Sensopad Technologies Limited Harston Mill Harston Cambridgeshire CB2 5GG.

HOWARD; Mark Anthony
c/o Sensopad Technologies Limited
Harston Mill
Harston
Cambridgeshire
CB2 5GG



The Patent <u>Office</u> Request for grant of a patent

The Patent Office Cardiff Road Newport

3.	Your reference 1882301/DJBB Patent Application Number O21987 Full name, address and postcode of the or of each applicant the state of the or of each applicant the state of the state o		197	
3.	Full name, address and postcode of the or of each applicant Sensopad Technologies Limited Harston Mill		127	AUG 200
	Full name, address and postcode of the or of each applicant Sensopad Technologies Limited Harston Mill		1.74 11	MINIT ZUL
	Harston Mill			
	Cambridgeshire CB2 5GG			
	Patents ADP number (if known) 81574710	ol =		
	If the applicant is a corporate body, give the country/state of its incorporation	ry: ENGLAND		
4.	Title of the invention	· · · · · · · · · · · · · · · · · · ·		
	CONCEPT FOR AUTOMOTIVE STEERING WHEEL	s		
5.	Name of agent	Beresford & Co		
	"Address for Service" in the United Kingdom to which all correspondence should be sent	2/5 Warwick Court High Holborn London WC1R 5DH		·
3	Patents ADP number / 22600			
5.	Priority details			
•	Country Priority application number	Date of filing		

Patents Form 1/77

7.	If this application is divided or otherwise de	erived from an earlier UK application give details
	Number of 1'	Date of filing
8.	Is a statement of inventorship and or right to	grant of a patent required in support of this
	•	1 wedaned in support of this
	YES	
9.	Enter the number of sheets for any of the fol	lowing items you are filing with this form.
	Continuation sheets of this	
	Description	3
	Claim(s)	0
	Abstract	o j
•	Drawing(s)	
10.	If you are also filing any of the following, sta	te how many against each it
	Priority documents	
	Translations of priority docu	ments o
	Statement of inventorship and	4
*	right to grant of a patent (Pat	ents form 7/77) 1 + 2 copies
	Request for preliminary exam and search (Patents Form 9/7	nination (7) 0
	Request for Substantive Fyan	
	(Patents Form 10/77)	0
•	Any other documents (please specify)	
11.	I/We request the grant of a patent on the basis of	
	Signature Berestond + Co	Date 27 August 2002
12.	Name and daytime telephone number of	·
	person to contact in the United Kingdom	BRINCK; David John Borchardt
		Tel: 020 7831 2290

Concept for Automotive Steering Wheels

Version 1.0

Authors - Bruce Macaulay & Mark Howard

1 INTRODUCTION

Sensopad Technologies' Freewheel[™] concept uses non-contact inductive sensing technology to produce lower cost controls on automotive steering wheels. The concept's focus is the radical simplification of the steering column's traditional Rotary Coupler. This complex and costly sub-assembly presently carries a large number of connections to and from the various steering wheel controls.

The electronics required to enable inductive communication between the rotating steering wheel and the stationary column also have the capability to control other adjacent elements such as stalk controls and steering column position memory sensors. Furthermore, high accuracy steering angle sensors can be integrated in to the FreewheelTM concept at small incremental cost.

2 AIM

This document aims to provide a technical overview of Sensopad Technologies' FreewheelTM concept for automotive steering wheels.

3 BACKGROUND


A recent trend in mid to high-end vehicles has been the increasing use of controls on the steering wheel itself in addition to than the more traditional placements of centre console, dashboard or door panel. The most frequent examples are:

- Radio volume, frequency and station controls
- Cruise controls
- Telephone controls
- Climate controls
- (Horn)


Although consumer feedback has shown to be positive, the provision of such controls comes at a cost to the vehicle manufacturer. A significant part of the cost is the provision of a complex Rotary Coupler sub-assembly in the vehicle's steering column. Further costs have been incurred from reliability problems.

4 FREEWHEEL™ CONCEPT

The Freewheel concept eradicates the need for a physical connection between the rotating steering wheel and the stationary steering column for all but Air bag firing signals. This allows the complexity of the interconnect to be radically simplified.



This is achieved by using inductive non-contact inductive sensing technology. Each switch on the steering wheel still contains a contacting electrical switch but rather than closing a circuit via the Rotary Coupler, the switch closes a resonant LC circuit (or 'puck') of a predefined frequency (or position relative to a known datum). The completion of the resonant circuit is sensed by a local, staitionary inductive antennae or 'pad'. Such pads are produced on a small printed circit board. A single pad may sense several such circuits.




Given the potential for radical simplification, further controls on the steering wheel become economically and technically more feasible, such as lighting or window controls and finger tip operated gear change.

5 BENEFITS

- Reduced costs
- Increased reliability
- Reduced noise and weight
- Greater design freedom (from reduced physical volume requirement) and the passive nature of the Steering wheel mounted controls

6 FURTHER OPPORTUNITIES FOR INCREASED FUNCTIONALITY & REDUCED COSTS

The processing electronics for the steering wheel controls can be used for a variety of additional functions. This provides for a very low cost system since the cost of additional pads and pucks for each sensed position is small.



Since such controls are contactless they provide high levels of reliability and design freedom. Wiring costs are also reduced because only a single serial data interface is required between the processing electronics and the vehicle's central electronic control unit.

FreewheelTH is a Trademark of Sensopad Technologies Ltd

Concept for Automotive Steering Wheels

Version 1.0

Authors - Bruce Macaulay & Mark Howard

1 INTRODUCTION

Sensopad Technologies' FreewheelTM concept uses non-contact inductive sensing technology to produce lower cost controls on automotive steering wheels. The concept's focus is the radical simplification of the steering column's traditional Rotary Coupler. This complex and costly sub-assembly presently carries a large number of connections to and from the various steering wheel controls.

The electronics required to enable inductive communication between the rotating steering wheel and the stationary column also have the capability to control other adjacent elements such as stalk controls and steering column position memory sensors. Furthermore, high accuracy steering angle sensors can be integrated in to the FreewheelTM concept at small incremental cost.

2 AIM

This document aims to provide a technical overview of Sensopad Technologies' FreewheelTM concept for automotive steering wheels.

3 BACKGROUND


A recent trend in mid to high-end vehicles has been the increasing use of controls on the steering wheel itself in addition to than the more traditional placements of centre console, dashboard or door panel. The most frequent examples are:

- Radio volume, frequency and station controls
- Cruise controls
- Telephone controls
- Climate controls
- (Horn)


Although consumer feedback has shown to be positive, the provision of such controls comes at a cost to the vehicle manufacturer. A significant part of the cost is the provision of a complex Rotary Coupler sub-assembly in the vehicle's steering column. Further costs have been incurred from reliability problems.

4 FREEWHEELTM CONCEPT

The Freewheel concept eradicates the need for a physical connection between the rotating steering wheel and the stationary steering column for all but Air bag firing signals. This allows the complexity of the interconnect to be radically simplified.



This is achieved by using inductive non-contact inductive sensing technology. Each switch on the steering wheel still contains a contacting electrical switch but rather than closing a circuit via the Rotary Coupler, the switch closes a resonant LC circuit (or 'puck') of a predefined frequency (or position relative to a known datum). The completion of the resonant circuit is sensed by a local, staitionary inductive antennae or 'pad'. Such pads are produced on a small printed circit board. A single pad may sense several such circuits.




Given the potential for radical simplification, further controls on the steering wheel become economically and technically more feasible, such as lighting or window controls and finger tip operated gear change.

5 BENEFITS

- Reduced costs
- Increased reliability
- Reduced noise and weight
- Greater design freedom (from reduced physical volume requirement) and the passive nature of the Steering wheel mounted controls

6 FURTHER OPPORTUNITIES FOR INCREASED FUNCTIONALITY & REDUCED COSTS

The processing electronics for the steering wheel controls can be used for a variety of additional functions. This provides for a very low cost system since the cost of additional pads and pucks for each sensed position is small.



Since such controls are contactless they provide high levels of reliability and design freedom. Wiring costs are also reduced because only a single serial data interface is required between the processing electronics and the vehicle's central electronic control unit.

Freewheel^{Tr.} Is a Trademark of Sensopad Technologies Ltd

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:		
BLACK BORDERS		
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES		
☐ FADED TEXT OR DRAWING		
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING		
☐ SKEWED/SLANTED IMAGES		
COLOR OR BLACK AND WHITE PHOTOGRAPHS		
☐ GRAY SCALE DOCUMENTS		
☐ LINES OR MARKS ON ORIGINAL DOCUMENT		
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY		
Потивъ		

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)